



MIDAS BathyPack



The MIDAS BathyPack is one of Valeport's premier MIDAS products, using state of the art sensors to generate precision Sound Velocity and Density profiles for highly accurate depth and height data. The simple top-end PC software, BathyLog, also allows all profile data to be used to monitor and correct multiple miniIPS pressure sensors, giving you the complete picture with one integrated sensor suite.

Sensors

Conductivity

Robust, accurate inductive cell. Digital sampling technique means no more field calibrations.

Range:	0 - 80 mS/cm
Accuracy:	±0.01 mS/cm
Resolution:	0.002 mS/cm

Temperature

Type:	Fast Response PRT with guard
Range:	-5 to +35 °C
Accuracy:	±0.005 °C
Resolution:	0.002 °C

Pressure

Revolutionary temperature compensated piezo-resistive sensor; all the performance of a resonant quartz sensor but with long term stability and better durability. No more oil!

Range:	10, 30, 100, 300 or 600Bar
Accuracy:	±0.01% range
Resolution:	0.001% range

Sound Velocity

Valeport's digital time of flight sensor - the most accurate SV sensor in the world.

Range:	1375 - 1900 m/s
Accuracy:	±0.02 m/s
Resolution:	0.001 m/s

Altimeter

BathyPack accepts a variety of industry standard devices. Typical specification - Valeport VA500 Altimeter:

Frequency:	500kHz
Range:	0 - 50 m (6000m depth rating)
Resolution:	1mm

Calculations

Density:	EOS-80 Equation of State of Seawater
Salinity:	PSS78 Practical Salinity Scale
Depth:	UNESCO Pressure/Depth Relationship or Simplified "Mean Density" Correction

Data Acquisition

Data Sampling:	2Hz
Lookup Table:	6000 points (1m res. @ max depth)
Sampling Sequence:	Synchronous



Communications

The instrument will operate by direct communications with PC before and after deployment. It also operates in real time, with a choice of communication protocols for a variety of cable lengths, all fitted as standard and selected by pin choice on the output connector:

Standard

RS232	Up to 200m cable, direct to serial port via USB adaptor
RS485	Up to 1000m cable, addressable half duplex comms
Baud Rate:	2400 - 115200
Protocol:	8 data bits, 1 stop bit, No parity, No flow control

Electrical

External Power:	12 - 30vDC
Power:	Nominal 4W max
Connector:	SubConn MCBH10F

Physical

Materials:	Titanium housing, polyurethane, composite and polycarbonate sensor components
Depth Rating:	6000m (may be limited by pressure sensor)
Instrument Size:	88mmØ x 425mm long
Weight:	6kg
Shipping:	74 x 35 x 27cm 13kg

Software

System is supplied with BathyLog Windows based PC software, for instrument setup and data display. BathyLog is licence free.

Ordering

0608002	MIDAS BathyPack in titanium Supplied with: • 3m interface lead • 0.5m altimeter input pigtail • BathyLog software • Manual and transit case.
Associated Products	
0760001	miniIPS Pressure Sensor
0430003	VA500 Altimeter